



# CLADIT+ SEMI GLOSS PC76

**A high performance two pack polyurethane finish for exterior cladding renovation.**

## Recommended Areas of Use

Exterior cladding requiring a hard wearing, flexible, weather and light resistant coating. Excellent adhesion to existing cladding coatings (coil, plastisol and powder coatings) with minimal preparation.

## Certificates & Approvals

Manufactured under the auspices of an ISO 9001:2008 quality & ISO 14001:2004 environmental management systems.

2004/42/EC EU limit value for this product (cat.A/d sb): 300g/l (2010). This product contains max.198 g/l VOC.

## Properties

<b>Gloss</b>	Semi-gloss (approx. 50%)	<b>Surface dry</b>	1 hour
<b>Theoretical Coverage</b>	10 m <sup>2</sup> /L/coat	<b>Minimum overcoating time</b>	12 hours minimum
<b>Recommended number of coats</b>	2 full coats	<b>Maximum overcoating time</b>	Unlimited
<b>Density</b>	1.24 kg/L	<b>Minimum application conditions</b>	Down to 0°C & 75% RH maximum (but must be 3°C above dew point)
<b>Volume solids</b>	53%	<b>Full cure</b>	7 days
<b>Flash point (Abel closed cup)</b>	28°C		
<b>VOC</b>	198 g/L	<b>Shelf life</b>	12 months minimum in original unopened containers.
<b>Thinner / Cleaning</b>	Bradite Thinner TP33	<b>Colour range</b>	RAL, British Standard
<b>Pot Life</b>	6 hours	<b>Mix Ratio</b>	Base & Activator tins are supplied pre-measured. For part mixing use: 7:1 (v/v) or 100:12 pbw
<b>Recommended wet film thickness</b>	100 microns/coat	<b>Recommended dry film thickness</b>	53 microns/coat

## Suitable Surfaces

Suitable for use over most existing cleaned and prepared cladding coating systems. Compatibility with existing coatings should be confirmed by preparing and painting a test patch. Bare steel and non-ferrous metals should be properly prepared and primed before painting with this product.

## Application Information

Always aim to paint an elevation preceding direct sunlight illumination to prevent painting onto warm surfaces which may cause too rapid drying and detract from application properties and finish appearance quality. Application and use should always conform to the codes of practice described in BS 6150 and BS 5493.

**Brush and Roller** – supplied ready for use. Thin with 0 - 10% Bradite Thinner TP33 if required.

**Conventional Air Spraying** - Thin with 10 - 20% Bradite Thinner TP33 as required, tip size - 2.0mm, tip pressure 60psi (0.4MPa) approximately.

**Airless Spraying** - Thin with 0 - 15% Bradite Thinner TP33 as required, tip size - 18 thou (0.46mm) approximately, tip pressure - 2100 psi (15MPa) approximately.

## Cleaning

Clean all equipment immediately after use with Bradite Thinner TP33 for best results.

## Specification

### Preparation

High pressure water cleaning to remove all loose and flaking paint and contamination back to a sound substrate. Bradite TD39 industrial strength detergent washing and rinsing should be used with scrubbing to remove grease or oil.

Check & confirm adhesion of apparently sound cladding coating by carrying out cross hatch adhesion test to all elevations. If adhesion is suspect then elevation should be completely stripped of old coating and repainted.

Intact areas of existing coatings should, ideally, be roughened by manual or mechanical sanding. Feather back exposed areas to a sound coating edge. Cracks and pits should be filled using a suitable filler before painting. Substrate should be dust free and completely dry before coating.

Exposed ferrous substrate should be blast cleaned to SIS Sa2<sup>1/2</sup> or manually cleaned to SIS St3, then patch primed with Bradite Surface Tolerant Epoxy Primer EP92\*.

### Painting System

Priming coat	Bradite Surface Tolerant Epoxy Primer EP92 [if required]*
1st coat	Bradite CLADIT+ Semi Gloss PC76
2nd coat	Bradite CLADIT+ Semi Gloss PC76

\* For non-ferrous surfaces use, Bradite Barrier Primer EU96 instead.

## Summary Safety Information

Always refer to the Health and Safety sheet for the product before use, and observe the warning phrases on the label.

**Disclaimer** - The information on this data sheet is correct to the best of our knowledge and experience. Bradite reserves the right to modify data contained herein, without notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service and application may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** CLADIT+ SEMI GLOSS

**Product code:** PC76

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers. For professional use only.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Bradite Paints  
Ogwen Valley Works  
Bethesda  
Gwynedd  
LL57 4YP  
United Kingdom

**Tel:** +44 (0)1248 600315

**Fax:** +44 (0)1248 602782

**Email:** [sales@bradite.com](mailto:sales@bradite.com)

### 1.4. Emergency telephone number

**Emergency tel:** +44 (0)1248 600315  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335

**Most important adverse effects:** Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause respiratory irritation. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

**Label elements:**

**Hazard statements:** H226: Flammable liquid and vapour.  
H304: May be fatal if swallowed and enters airways.  
H335: May cause respiratory irritation.  
H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame  
GHS07: Exclamation mark  
GHS08: Health hazard  
GHS09: Environmental

# SAFETY DATA SHEET

CLADIT+ SEMI GLOSS

Page: 2



**Signal words:** Danger

**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+310: IF SWALLOWED: Immediately call a.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	10-30%

1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
-----------	---------	---	---	-------

DI-N-BUTYLTIN DILAURATE - REACH registered number(s): 01-2119496068-27-XX

201-039-8	77-58-7	-	Skin Irrit. 2: H315; STOT RE 2: H373; Aquatic Chronic 1: H410; Eye Irrit. 2: H319	<1%
-----------	---------	---	---	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

CLADIT+ SEMI GLOSS

Page: 3

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Do not use water.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from sources of ignition.

**Suitable packaging:** Must only be kept in original packaging.

**Storage quantity limits:** 250 L

[cont...]

# SAFETY DATA SHEET

CLADIT+ SEMI GLOSS

Page: 4

## 7.3. Specific end use(s)

**Specific end use(s):** PC9a: Coatings and paints, thinners, paint removers.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**1,2,4-TRIMETHYLBENZENE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	125 mg/m <sup>3</sup>	-	-	-

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141).

**Hand protection:** Gloves (solvent-resistant).

**Eye protection:** Tightly fitting safety goggles.

**Skin protection:** Protective clothing with elasticated cuffs and closed neck.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Various

**Odour:** Characteristic odour

**Evaporation rate:** Slow

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Not miscible

**Also soluble in:** Most organic solvents.

**Viscosity:** Non-viscous

**Boiling point/range°C:** 162 - 181

**Melting point/range°C:** No data available.

**Flammability limits %: lower:** 0.8

**upper:** 7.5

**Flash point°C:** 43

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** 450

**Vapour pressure:** 0.29 kPa @ 20 deg C

**Relative density:** 1.27

**pH:** Not applicable.

**VOC g/l:** 189

[cont...]

# SAFETY DATA SHEET

CLADIT+ SEMI GLOSS

Page: 5

## 9.2. Other information

Other information: Not applicable.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

Conditions to avoid: Direct sunlight.

### 10.5. Incompatible materials

Materials to avoid: Strong acids. Strong bases. Strong oxidising agents.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Hazardous ingredients:

**LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.**

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

**1,2,4-TRIMETHYLBENZENE**

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

**DI-N-BUTYLTIN DILAURATE**

ORAL	RAT (female)	LD50	3312	mg/kg
ORAL	RAT (male)	LD50	1976	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
STOT-single exposure	INH	Hazardous: calculated

[cont...]

# SAFETY DATA SHEET

CLADIT+ SEMI GLOSS

Page: 6

Aspiration hazard	-	Hazardous: calculated
-------------------	---	-----------------------

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Other information:** Not applicable.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

#### DI-N-BUTYL TIN DILAURATE

Daphnia magna	48H EC50	0.66	mg/l
FISH	96H LC50	2	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** No data available.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Solvent reclamation/regeneration.

**Waste code number:** 08 01 11

**Disposal of packaging:** Retain for recovery.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]



# SAFETY DATA SHEET

CLADIT+ SEMI GLOSS

Page: 7

## Section 14: Transport information

### 14.1. UN number

UN number: UN1263

### 14.2. UN proper shipping name

Shipping name: PAINT

### 14.3. Transport hazard class(es)

Transport class: 3

### 14.4. Packing group

Packing group: III

### 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that

[cont...]

## SAFETY DATA SHEET

CLADIT+ SEMI GLOSS

Page: 8

no other routes of exposure cause the hazard>.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** 2K PU ACTIVATOR (PG77, PC76, PL78)

**Product code:** See above

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers. For professional use only.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Bradite Paints  
Ogwen Valley Works  
Bethesda  
Gwynedd  
LL57 4YP  
United Kingdom

**Tel:** +44 (0)1248 600315

**Fax:** +44 (0)1248 602782

**Email:** [sales@bradite.com](mailto:sales@bradite.com)

### 1.4. Emergency telephone number

**Emergency tel:** +44 (0)1248 600315  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** STOT SE 3: H335; Acute Tox. 4: H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317

**Most important adverse effects:** Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause respiratory irritation.

### 2.2. Label elements

**Label elements:**

**Hazard statements:** H226: Flammable liquid and vapour.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H332: Harmful if inhaled.  
H335: May cause respiratory irritation.

**Signal words:** Warning

# SAFETY DATA SHEET

2K PU ACTIVATOR (PG77, PC76, PL78)

Page: 2

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark



**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/soap and water.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPLOYMER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	28182-81-2	-	STOT SE 3: H335; Acute Tox. 4: H332; Skin Sens. 1: H317	70-90%

2-METHOXY-1-METHYLETHYL ACETATE - REACH registered number(s): 01-2119475791-29

203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	10-30%
-----------	----------	--	--------------------	--------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	---	-------

ETHYLBENZENE

202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1-10%
-----------	----------	---	--	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

2K PU ACTIVATOR (PG77, PC76, PL78)

Page: 3

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Do not use water.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 13 of SDS.

## Section 7: Handling and storage

[cont...]

# SAFETY DATA SHEET

2K PU ACTIVATOR (PG77, PC76, PL78)

Page: 4

## 7.1. Precautions for safe handling

**Handling requirements:** Do not handle in a confined space. Smoking is forbidden.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from sources of ignition.

**Suitable packaging:** Must only be kept in original packaging.

**Storage quantity limits:** 250 L

## 7.3. Specific end use(s)

**Specific end use(s):** PC9a: Coatings and paints, thinners, paint removers.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPLOYMER**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-

**2-METHOXY-1-METHYLETHYL ACETATE**

UK	274 mg/m <sup>3</sup>	548 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

**XYLENE**

UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

**ETHYLBENZENE**

UK	441 mg/m <sup>3</sup>	552 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141).

**Hand protection:** Gloves (solvent-resistant).

**Eye protection:** Tightly fitting safety goggles.

**Skin protection:** Protective clothing with elasticated cuffs and closed neck.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

[cont...]

# SAFETY DATA SHEET

2K PU ACTIVATOR (PG77, PC76, PL78)

Page: 5

**Odour:** Sweet-smelling

**Evaporation rate:** Slow

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Reacts with water.

**Also soluble in:** Most organic solvents.

**Viscosity:** Non-viscous

**Boiling point/range°C:** 145

**upper:** 10.8

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** 8 hPa @ 20 deg C

**pH:** Not applicable.

**Flammability limits %: lower:** 1,5

**Flash point°C:** 38

**Autoflammability°C:** 460

**Relative density:** 1.07

**VOC g/l:** 268

## 9.2. Other information

**Other information:** Not applicable.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

**Conditions to avoid:** Direct sunlight. Sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid:** Strong acids. Strong bases. Strong oxidising agents. Water.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

**HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPLOYMER**

ORAL	RAT	LD50	>5000	mg/kg
------	-----	------	-------	-------

[cont...]

## SAFETY DATA SHEET

2K PU ACTIVATOR (PG77, PC76, PL78)

Page: 6

### 2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

### XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

### ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	mg/kg

#### Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

#### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Other information:** Not applicable.

#### Section 12: Ecological information

##### 12.1. Toxicity

#### Hazardous ingredients:

##### HEXAMETHYLENE-1,6-DIISOCYANATE HOMOPLOYMER

ALGAE	72H ErC50	>100	mg/l
Daphnia magna	48H EC50	>100	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	>100	mg/l

##### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

[cont...]



**SAFETY DATA SHEET**  
2K PU ACTIVATOR (PG77, PC76, PL78)

Page: 7

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No data available.

**12.4. Mobility in soil**

**Mobility:** No data available.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** No data available.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Solvent reclamation/regeneration.

**Waste code number:** 08 01 11

**Disposal of packaging:** Retain for recovery.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN1263

**14.2. UN proper shipping name**

**Shipping name:** PAINT

**14.3. Transport hazard class(es)**

**Transport class:** 3

**14.4. Packing group**

**Packing group:** III

**14.5. Environmental hazards**

**Environmentally hazardous:** No

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 3

[cont...]

# SAFETY DATA SHEET

2K PU ACTIVATOR (PG77, PC76, PL78)

Page: 8

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.