# LOW SLIP ADDITIVE - AGGREGATE LS30



# A hard Aluminium Oxide aggregate additive providing additional under foot traction to floor coatings

#### **Recommended Areas of Use**

Used in conjunction with Bradite floor paints requiring a hard wearing low slip additive.

## **Certificates & Approvals**

Manufactured under the auspices of an ISO 9001:2008 quality & ISO 14001:2004 environmental management systems.

### **Properties**

Theoretical spreading rate	0.25 to 1.0 kg/m <sup>2</sup>	Shelf life	Unlimited in original unopened containers
Density	3.77 kg/L	Colour range	Light grey
Volume solids	100%	Particle Size	Approximately 0.1 mm

#### Suitable Surfaces

Consult technical datasheet for the specific Bradite floor paint product for recommendations.

# **Application Information**

Consult technical datasheet for the specific Bradite floor paint product for recommendations.

# Incorporation

This additive may be incorporated into the paint by direct incorporation providing a more even appearance on large areas.

DIncorporation

Bradite Low Slip Soft Aggregate LS30 should be added to the paint and mixed thoroughly just before use at a rate of 1 x 250ml LS30 tin (400g) per 5 litre of paint.

The end user and applicator must ensure that the finished floor is safe against slips in all likely usage conditions.

# **Summary Safety Information**

Always refer to the Health and Safety sheet for the product before use, and observe the warning phrases on the label.

**Disclaimer -** The information on this data sheet is correct to the best of our knowledge and experience. Bradite reserves the right to modify data contained herein, without notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service and application may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.



LOW SLIP ADDITIVE - ALUMINIUM OXIDE

Page: 1

Compilation date: 24/07/2019

Revision No: 1

#### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: LOW SLIP ADDITIVE - ALUMINIUM OXIDE

Product code: LS30

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

#### 1.3. Details of the supplier of the safety data sheet

Company name: Bradite Paints

Ogwen Valley Works

Bethesda Gwynedd LL57 4YP

United Kingdom

Tel: +44 (0)1248 600315
Fax: +44 (0)1248 602782
Email: sales@bradite.com

#### 1.4. Emergency telephone number

Emergency tel: +44 (0)1248 600315

(office hours only)

#### **Section 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

#### 2.2. Label elements

Label elements: This product has no label elements.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

#### Section 3: Composition/information on ingredients

#### 3.1. Substances

Chemical identity: LOW SLIP ADDITIVE - ALUMINIUM OXIDE

#### Section 4: First aid measures

#### LOW SLIP ADDITIVE - ALUMINIUM OXIDE

Page: 2

#### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. **Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

#### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Not applicable.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Not applicable.

#### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

**Handling requirements:** Avoid the formation or spread of dust in the air.

LOW SLIP ADDITIVE - ALUMINIUM OXIDE

Page: 3

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.Suitable packaging: Must only be kept in original packaging.

Storage quantity limits: N/A

#### 7.3. Specific end use(s)

**Specific end use(s):** PC9a: Coatings and paints, thinners, paint removers.

#### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: No data available.

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

#### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles.

Skin protection: Protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

#### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State: Solid Colour: White

Odour: Odourless

Evaporation rate: Not applicable.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Boiling point/range°C: Not applicable. Melting point/range°C: Not applicable.

Flammability limits %: lower: Not applicable. upper: Not applicable.

Flash point°C: Not applicable. Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable. Vapour pressure: Not applicable.

Relative density: 3.77 kg/L pH: Not applicable.

VOC g/l: Not applicable.

#### 9.2. Other information

Other information: No data available.

#### LOW SLIP ADDITIVE - ALUMINIUM OXIDE

Page: 4

#### Section 10: Stability and reactivity

10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: Not applicable.

#### **Section 11: Toxicological information**

#### 11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Other information: Not applicable.

#### **Section 12: Ecological information**

#### 12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

LOW SLIP ADDITIVE - ALUMINIUM OXIDE

Page: 5

#### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: No data available.

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal operations:** Deposit into or on to land (e.g. landfill, etc.)

Recovery operations: Not applicable.

Waste code number: 08 02 01

Disposal of packaging: Retain for recovery.

**NB:** The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

#### **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

#### **Section 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

#### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### Section 16: Other information

#### Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.