



# HD FLOOR + WALL EW99

## A high-performance, two-pack, water-based smooth epoxy floor and wall coating

### Recommended Areas of Use

Interior concrete, wood or steel floors requiring a tough, quick drying, hard-wearing flexible floor coating with good chemical and excellent water resistance. Can be used with Bradite Low Slip Additive LS30 to provide additional under foot traction (see Notes section for more details).

### Certificates & Approvals

Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems.

2004/42/EC EU limit value for this product (cat.A/b wb): 100g/l (2010). This product contains max.2 g/l VOC. BS 476 Part 6 & 7: Fire propagation index, I; 2.5, Surface spread of flame; Class 1, Building Regulations 1991, "Fire Safety", Document B [para. A12(b)]: Class 0.

### Properties

<b>Gloss</b>	Full (> 75%)	<b>Surface dry</b>	3 hours
<b>Theoretical Coverage</b>	13 m <sup>2</sup> /L/coat	<b>Minimum over coating time</b>	14 hours minimum
<b>Recommended number of coats</b>	2 full coats (on bare absorbent surfaces, apply a 20% thinned priming coat first).	<b>Maximum over coating time</b>	Unlimited (after preparation)
<b>Density</b>	1.18 kg/L	<b>Minimum application conditions</b>	Temperature > 10°C, RH < 65% (but must be 3°C above dew point)
<b>Volume solids</b>	57% (mixed)	<b>Time to light traffic</b>	24 hours minimum, after final coat
<b>Flash point (Abel closed cup)</b>	>99°C	<b>Full cure</b>	6 days
<b>VOC</b>	<2 g/L	<b>Shelf life</b>	12 months minimum in original unopened containers.
<b>Thinner / Cleaning</b>	Water	<b>Colour range</b>	Light Grey, Dark Grey, Yellow stock colours, RAL, British Standard and NCS & Clear
<b>Pot Life</b>	1 hour	<b>Mix Ratio</b>	Base & Activator tins are supplied pre-measured. For part mixing use: 2:1 (v/v) or 100:44 pbw
<b>Recommended wet film thickness</b>	100 microns/coat	<b>Recommended dry film thickness</b>	57 microns/coat

## Suitable Surfaces

For internal use only on steel, wood, concrete and other absorbent mineral substrates which are dry, free of contamination, dust, efflorescence and have been properly prepared and primed. Compatibility with existing coatings should be confirmed by preparing and painting a test patch. [Note, not suitable for applying over asphalt, bitumen, epoxy tar, alkyd, chlorinated rubber or vinyl based paints, or for use in areas that are cleaned with iodine.]

## Application Information

Thin first coat on new or uncoated concrete, wood or plaster by 20-30% to enable penetration and binding of substrate. Application and use should always conform to the codes of practice described in BS 6150 and BS 5493.

**Brush and Roller** – Supplied ready for use. Thin, if required, with 0 - 5% water. On smooth substrates, the use of a short pile roller is advised. (Guidelines only).

**Conventional Air Spraying** - Thin with 10 - 20% clean water as required, tip size - 2.0mm, tip pressure 60psi (0.4MPa) approximately. (Guidelines only).

**Airless Spraying** - Thin with 10-20% clean water as required, tip size - 18 thou (0.46mm) approximately, tip pressure - 2100 psi (15MPa) approximately.

## Cleaning

Clean all equipment with water immediately after use for best results.

## Specification

New Building, Total Repair and Maintenance systems using two pack epoxy coating, Bradite HD Floor + Wall EW99.

## Floor Preparation

Substrates should be dust free and completely dry before coating. When painting concrete, it is vital to ensure that the substrate is completely dry and free of laitance. Power floated, shiny or unpainted, non-porous concrete floors should be thoroughly vacuum blast cleaned to a roughness profile of 30-50 microns, or acid etched using Bradite Acid Etch TA37. Please consult the product data sheet for more details.

High pressure water cleaning should be utilised to remove all loose and flaking paint and contamination back to a sound substrate. Bradite Industrial Degreaser TD39 should be used to remove all grease and oil. A second clean may be required to remove more stubborn stains (oil/grease).

Intact areas of existing coatings should be roughened by abrasive manual or disc rubbing and feathered back to a sound coating edge. Cracks and pits should be filled using a suitable screed or mortar before painting. Substrate should be dust free and completely dry before coating.

## Painting System

For application on concrete, wood or other absorbent substrates, the first coat should be thinned with 10-20% water to allow penetration into the substrate.

1st coat	Bradite HD Floor + Wall EW99 (thinned)
2nd coat	Bradite HD Floor + Wall EW99
3rd coat	Bradite HD Floor + Wall EW99

For maintenance, painting the first coat will be a touch up to bare areas.

## Wall Preparation - New building Or Total Repair

When painting new plaster, it is vital to ensure the substrate is fully cured and free of laitance.

Cracks and pits should be filled using a suitable filler before painting. Remove all loose and flaking paint back to a sound substrate. High gloss coatings should be abraded to provide a mechanical key. Substrate should be dust free and completely dry before coating. Bradite Industrial Degreaser TD39 should be used with scrubbing, washing and rinsing to remove grease or oil.

## Painting System

For application on plaster or other absorbent substrates, the first coat should be thinned with 10-20% water to allow penetration into the substrate.

1st coat	Bradite HD Floor + Wall EW99 (thinned)
2nd coat	Bradite HD Floor + Wall EW99
3rd coat	Bradite HD Floor + Wall EW99

For maintenance, painting the first coat will be a touch up to bare areas.

## Notes

Bradite HD Floor + Wall EW99 is suitable for use with Bradite Low Slip Additive LS30, which can be incorporated into the paint.

Bradite Low Slip Hard Aggregate LS30 should be added to the paint and mixed thoroughly just before use at a rate of 1 x 250ml LS30 tin (400g) per 5 litre of paint.

The end user and applicator must ensure that the finished floor is safe against slips in all likely usage conditions.

Risk of Slip	PTV
High	0-24
Moderate	25-35
Low	36+

Sample	Test	Temperature	Average Pendulum Test Value		Risk of Slip	
	Direction		Dry	Wet/Water	Dry	Wet
EW99	0°	23°C	48.3	21.7	Low	High
EW99 + 10% Low Slip Additive	0°	23°C	58.3	31.7	Low	Moderate
EW99 + 20% Low Slip Additive	0°	23°C	63.3	50.0	Low	Low
EW99 + 30% Low Slip Additive	0°	23°C	68.3	55.0	Low	Low

## Industrial Protective Coating Preparation

High pressure steam cleaning to remove all loose, flaking paint and contamination back to a sound surface. Use Bradite Industrial Degreaser TD39, washing and rinsing along with scrubbing to remove grease or oil.

For new or total repair, steel should be blast cleaned to SIS Sa 2<sup>1/2</sup> minimum with a blast profile of 35-50 microns. (For maintenance repair, sweep blast or mechanically abrade existing coating to provide a key. Damaged or rusty areas should be blast cleaned to SIS Sa 2<sup>1/2</sup> or mechanically to SIS St 3 minimum).

1st coat	Bradite HD Floor + Wall EW99 (thinned)
2nd coat	Bradite HD Floor + Wall EW99
3rd coat	Bradite HD Floor + Wall EW99

For maintenance, painting the first coat will be a touch up to bare areas only.

## Notes

This system is recommended for internal protection and decoration only. Epoxy systems will chalk on external exposure to sunlight, resulting in loss of gloss and colour fade.

## Summary Safety Information

Always refer to the Health and Safety sheet for the product before use, and observe the warning phrases on the label.

**Disclaimer** - The information on this data sheet is correct to the best of our knowledge and experience. Bradite reserves the right to modify data contained herein, without notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service and application may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Mixture
Product name	: HD FLOOR & WALL
Product code	: EW99
Type of product	: Paint
Product group	: End product

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category	: Consumer use
Function or use category	: Coatings and paints, thinners, paint removers

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Bradite Paints  
Ogwen Valley Works  
Bethesda Gwynedd  
LL57 4YP  
T +44 (0)1248 600315 - F +44 (0)1248 602782  
[sales@bradite.com](mailto:sales@bradite.com)

**1.4. Emergency telephone number**

Emergency number : +44 (0)1248 600315

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**


Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412
Full text of H- and EUH-statements: see section 16	

**Adverse physicochemical, human health and environmental effects**

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: FORMALDEHYDE, POLYMER WITH N1-(2-AMINOETHYL)-N2-[2-AMINOETHYL)AMINO]ETHYL]-1,2-ETHANEDIAMINE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLE), O,O'-BIS(2-AMINOPROPYL)POLYPROPYLENEGLYCOL, 3,6,9-TRIAZAUNDECAMETHYLENEDIAMINE

# HD FLOOR & WALL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P302+P352 - IF ON SKIN: Wash with plenty of water.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
FORMALDEHYDE, POLYMER WITH N1-(2-AMINOETHYL)-N2-[2-AMINOETHYL)AMINO]ETHYL]-1,2-ETHANEDIAMINE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLE)	CAS-No.: 180583-06-6	10 – 30	Skin Sens. 1, H317 Aquatic Chronic 2, H411
O,O'-BIS(2-AMINOPROPYL)POLYPROPYLENEGLYCOL	CAS-No.: 9046-10-0 EC-No.: 618-561-0	< 5	Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
3,6,9-TRIAZAUNDECAMETHYLENEDIAMINE	CAS-No.: 112-57-2 EC-No.: 203-986-2 EC Index-No.: 612-060-00-0	< 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Skin Corr. 1A, H314 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

# HD FLOOR & WALL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable.  
Explosion hazard : No direct explosion hazard.  
Reactivity in case of fire : Product is not explosive.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### 7.3. Specific end use(s)

Coatings and paints, thinners, paint removers.

# HD FLOOR & WALL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

No additional information available

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

No additional information available

##### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

##### 8.2.1. Appropriate engineering controls

###### Appropriate engineering controls:

Ensure good ventilation of the work station.

##### 8.2.2. Personal protection equipment

###### Personal protective equipment symbol(s):



###### 8.2.2.1. Eye and face protection

###### Eye protection:

Safety glasses

###### 8.2.2.2. Skin protection

###### Skin and body protection:

Wear suitable protective clothing

###### Hand protection:

Protective gloves

###### 8.2.2.3. Respiratory protection

###### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

###### 8.2.2.4. Thermal hazards

No additional information available

##### 8.2.3. Environmental exposure controls

###### Environmental exposure controls:

Avoid release to the environment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Various.
Odour	: Barely perceptible odour.



# HD FLOOR & WALL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Odour threshold	: No data available
pH	: ≈ 8.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: ≈ 0 °C
Boiling point	: ≈ 100 °C
Flash point	: > 100 °C
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: ≈ 1.21 kg/l
Solubility	: Miscible with water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: ≈ 107.44 mm <sup>2</sup> /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : ≈ 3 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation. pH: ≈ 8.5
Serious eye damage/irritation	: Causes serious eye damage. pH: ≈ 8.5
Respiratory or skin sensitisation	: May cause an allergic skin reaction.

# HD FLOOR & WALL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

### HD FLOOR & WALL

Viscosity, kinematic	≈ 107.44 mm <sup>2</sup> /s
----------------------	-----------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
Not rapidly degradable	

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code	: 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

# HD FLOOR & WALL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

#### Inland waterway transport

Not regulated

#### Rail transport

Not regulated

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### VOC Directive (2004/42)

VOC content :  $\approx 3$  g/l

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

# HD FLOOR & WALL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

##### Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
- Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids.
- Joint storage table :
- |          |         |          |          |           |
|----------|---------|----------|----------|-----------|
| LGK 1    | LGK 2A  | LGK 2B   | LGK 3    | LGK 4.1A  |
| LGK 4.1B | LGK 4.2 | LGK 4.3  | LGK 5.1A | LGK 5.1B  |
| LGK 5.1C | LGK 5.2 | LGK 6.1A | LGK 6.1B | LGK 6.1C  |
| LGK 6.1D | LGK 6.2 | LGK 7    | LGK 8A   | LGK 8B    |
| LGK 10   | LGK 11  | LGK 12   | LGK 13   | LGK 10-13 |
- Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7.
- Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C.
- Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13.
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

##### Netherlands

- ABM category : A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic environment
- SZW-lijst van kankerverwekkende stoffen : None of the components are listed
- SZW-lijst van mutagene stoffen : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

##### Denmark

- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

##### Switzerland

- Storage class (LK) : LK 10/12 - Liquids

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)

# HD FLOOR & WALL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Abbreviations and acronyms:	
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.

# HD FLOOR & WALL

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Sens. 1	Skin sensitisation, Category 1

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.