



ONE CAN OC63 - MATT

A quick drying, low odour, cross linking, water thinned primer/finish coat, with excellent adhesion, stain blocking and anti-corrosive properties.

Recommended Areas of Use

For use as a low-odour, quick-drying, scuff and moisture resistant, adhesion promoting, stain-locking, anti-corrosive coating for interior or exterior walls and trim, masonry (Brickwork/Concrete etc) ferrous metals, non-ferrous metals, common plastics (e.g. melamine and uPVC), ceramic tiles, glass, wood and existing painted surfaces. Offers a hard-wearing, flexible coating with weather and light resistance, ideal for use over existing cladding coatings (coil, plastisol and powder coatings) with minimal preparation.

Certificates & Approvals

Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems. 2004/42/EC EU limit value for this product (Annex IIA/i. wb): 140g/l (2010). This product contains max 30 g/l VOC.

Properties

Gloss	Matt (approx. 8%)	Surface dry	30 Minutes
Theoretical Coverage	11 m ² /L/coat	Minimum over coating time	1 hour minimum*
Recommended number of coats	2 coats minimum as a finish 3 coats for stain locking	Maximum over coating time	Unlimited
Density	1.34 kg/L	Minimum application conditions	10°C or above for application (minimum of 3°C above dew point)
Volume solids	41%	Full Cure	7 days
Flash point (Abel closed cup)	Non-Flammable	Shelf life	2 years minimum in original unopened containers.
VOC	25 g/L	Colour range	White & Black standard colours, RAL, British Standard, NCS.
Thinner / Cleaning	Water		
Recommended wet film thickness	75-100 microns/coat	Recommended dry film thickness	40 microns/coat

Suitable Surfaces

Suitable for use over most properly cleaned and prepared interior and exterior commercial wood, plastic and metals. Compatibility with existing coatings should be confirmed by preparing and painting a test patch. Fully anti-corrosive for application to ferrous and non-ferrous metals which have been properly prepared. Seals most stains in the primer coat, including water, nicotine, hardwood resin bleed, asphalt, and many more.

Application Information

*Drying times will be prolonged at lower temperatures and over application.

All surfaces must be dry and dust free before coating. Application should always conform with the codes of practice described in BS 6150 and BS 5493.

Brush and Roller - Supplied ready for use. Thin with 5-15% water if required.

Conventional Air Spraying - Thin with 5-15% water as required. Tip size - 2.0mm.

Tip pressure - 60psi (0.4MPa) approximately. (Guidelines Only).

Airless Spraying - Thin with 5-15% water as required. Tip size - 19 thou (0.48mm) approximately

Tip pressure - 2100 psi (15MPa) approximately. (Guidelines Only).

Cleaning

Equipment should be cleaned immediately after use with water.

Specifications

Surface Preparation

Loose and non-adhered coatings should be removed. Cleaning using Bradite Industrial Degreaser TD39 or methylated spirit is recommended to remove oils, grease and other contamination.

Intact areas of existing coatings should, ideally, be roughened by manual or mechanical sanding. Feather back any exposed areas to a sound coating edge. Cracks and pits should be filled using a suitable filler before painting. Substrate should be dust free and completely dry before coating.

Stain locking: Encapsulates stains in the primer coat, application of second coat will be required to hide, and in extreme cases a third coat may be required. One Can should be allowed to hard dry prior to overcoating. This will take at least one hour, over application may result in longer drying times

Aluminum, stainless steel, galvanised steel, copper and other metals: Cleaned and degreased with methylated spirit, and lightly abraded if possible. White salts on weathered galvanising must be removed during cleaning and degreasing. Light surface rusting should be treated with Bradite Rust Convertor RC46. Heavy rusting to be removed to clean metallic finish (SIS-St 3).

New Wood: Ensure moisture content of the timber is below 15% before commencing application. Damp wood should never be painted as this may give rise to blistering, flaking, cracking and premature coating failure. Knots to be wiped using methylated spirit, for heavy or active knots spot prime with aluminium wood primer.

Hard Woods: Wipe with methylated spirit to remove excess resin, changing the face of the cloth regularly. Lightly abrade.

Green oak: Should not be painted unless it has been weathered for at least 6 months.

Exterior cladding, powder coated, Varnish and Existing paint finish: Remove all loose and flaking paintwork. Degrease using Bradite Industrial Degreaser TD39, followed by clean water rinse. Rub down thoroughly with a medium grade sandpaper to provide a key and a defect free smooth surface, "feathering in" areas where paint has been removed.

UPVC, Formica, Melamine and Plastics: For long term performance, degrease using Bradite Industrial Degreaser TD39 or methylated spirit & lightly abrade surfaces.

New plaster walls: For plaster skim, allow at least four weeks for the plaster to thoroughly dry. Apply a primer coat by thinning the paint with a 5 to 25% (v/v) addition of clean water, depending upon the porosity of the substrate. Cut in by brushing at the same dilution recommendation as for priming, to promote flow and sealing of the substrate.

For new, fully plastered walls, allow at least six months for the plaster to thoroughly dry before painting.

This product is not recommended for painting lime or other natural plasters.

Masonry, brick, concrete: Clean, dry and free of contamination, existing coatings to be sound and well adhered. Any loose flaking material should be removed and sanded back to a sound, well-feathered edge. New concrete or masonry to be fully cured. Mould or mildew to be removed and area treated with good quality fungicidal wash following manufacturer's instructions.

Painting System

1st coat	Bradite ONE CAN OC64
2nd coat	Bradite ONE CAN OC64
3rd coat	Bradite ONE CAN OC64 [If required]

Summary Safety Information

Always refer to the Health and Safety sheet for the product before use, and observe the warning phrases on the label. In general, avoid inhalation of spray mist and skin contact by the use of masks, gloves and other personal protection. Eyes should be copiously washed with water or proprietary wash, and medical attention obtained. Skin should be thoroughly washed using a cleanser and soap and water.

Disclaimer - The information on this data sheet is correct to the best of our knowledge and experience. Bradite reserves the right to modify data contained herein, without notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service and application may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Mixture
Product name	: ONE CAN MATT
Product code	: OC63
Type of product	: Paint
Product group	: End product

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category	: Consumer use
Function or use category	: Coatings and paints, thinners, paint removers

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Bradite Paints
Ogwen Valley Works
Bethesda Gwynedd
LL57 4YP
T +44 (0)1248 600315 - F +44 (0)1248 602782
sales@bradite.com

1.4. Emergency telephone number

Emergency number	: +44 (0)1248 600315
------------------	----------------------

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP)

:



GHS09

Signal word (CLP)

: -

Hazard statements (CLP)

: H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P273 - Avoid release to the environment.

P391 - Collect spillage.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH208 - Contains A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9). May produce an allergic reaction.

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Advanced Micro Matrix Embedding (AMME™) technology: Algicide/Fungicide based on following substances: Terbutryn, pyrithione zinc, 2-Octyl-2H-isothiazol-3-one, zinc oxide, 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
TRIZINC BIS(ORTHOPHOSPHATE)	CAS-No.: 7779-90-0 EC-No.: 231-944-3 EC Index-No.: 030-011-00-6 REACH-no: 01-2119485044-40	< 5	STOT RE 2, H373 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
ZINC OXIDE	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030-013-00-7 REACH-no: 01-2119463881-32	< 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
POLYPROPYLENE GLYCOL	CAS-No.: 25322-69-4 EC-No.: 500-039-8	< 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 2 (Inhalation:dust,mist), H330 (ATE=0.05 mg/l/4h)
PYRITHIONE ZINC	CAS-No.: 13463-41-7 EC-No.: 236-671-3 EC Index-No.: 613-333-00-7	0.018 (0.0018)	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)
TERBUTRYN	CAS-No.: 886-50-0 EC-No.: 212-950-5	0.016 (0.0016)	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] substance with national workplace exposure limit(s) (AT, CH)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	< 5	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) EUH071

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-OCTYL-2H-ISOTHIAZOL-3-ONE	CAS-No.: 26530-20-1 EC-No.: 247-761-7 EC Index-No.: 613-112-00-5	0.009 (0.0009)	Acute Tox. 4 (Oral), H302 (ATE=550 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=690 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) EUH071
1,2-BENZISOTHIAZOLIN-3-ONE	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	< 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
2-METHYLISOTHIAZOL-3(2H)-ONE	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50	< 5	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 1 (Inhalation), H330 (ATE=0.005 mg/l/4h) Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1) EUH071

Specific concentration limits:

Name	Product identifier	Specific concentration limits
A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6]	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	(0.0015 ≤C < 100) Skin Sens. 1, H317 (0.06 ≤C ≤ 0.6) Skin Irrit. 2, H315 (0.06 ≤C ≤ 0.6) Eye Irrit. 2, H319 (0.6 ≤C < 100) Skin Corr. 1B, H314
2-OCTYL-2H-ISOTHIAZOL-3-ONE	CAS-No.: 26530-20-1 EC-No.: 247-761-7 EC Index-No.: 613-112-00-5	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317
1,2-BENZISOTHIAZOLIN-3-ONE	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	(0.05 ≤C < 100) Skin Sens. 1, H317
2-METHYLISOTHIAZOL-3(2H)-ONE	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Comments : Contains 2-methylisothiazol-3(2H)-one and 1,2-benzisothiazol-3(2H)-one to maintain storage stability. The percentages "total (free)%" of terbutryn are indicated. The free proportion is subject to the classification of the mixture with regard to environmentally hazardous properties, sensitisation. The percentages "total (free)%" of 2-octyl-2H-isothiazol-3-one are indicated. The free proportion is subject to the classification of the mixture with regard to environmentally hazardous properties, skin and eye irritation, sensitisation. The percentages "total (free)%" of pyriithione zinc are indicated. The free proportion is subject to the classification of the mixture with regard to environmentally hazardous properties, skin and eye irritation. Hazard statements see section 16

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

Coatings and paints, thinners, paint removers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)

Austria - Occupational Exposure Limits

Local name	5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-di-hydroisothiazol-3-on (Gemisch im Verhältnis 3:1)
MAK (OEL TWA)	0.05 mg/m ³
Remark	Sh
Regulatory reference	BGBl. II Nr. 156/2021

Switzerland - Occupational Exposure Limits

Local name	2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle et 2,3-dihydro-isothiazol-3-one de 2-méthyle [2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle, 2,3-Dihydro-isothiazol-3-one de 2-méthyle] / 5-Chlor-2-methyl-2,3-dihydro-isothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on [2-Methyl-2,3-dihydroisothiazol-3-on, 5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on]
MAK (OEL TWA) [1]	0.2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	0.4 mg/m ³ (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge
Notation	S, SS _C / S, SS _C
Regulatory reference	www.suva.ch, 28.03.2022

2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)

Austria - Occupational Exposure Limits

Local name	2-Methyl-2,3-di-hydroisothiazol-3-on
MAK (OEL TWA)	0.05 mg/m ³
Remark	Sh
Regulatory reference	BGBl. II Nr. 156/2021

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)

Switzerland - Occupational Exposure Limits

Local name	2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle et 2,3-dihydro-isothiazol-3-one de 2-méthyle [2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle, 2,3-Dihydro-isothiazol-3-one de 2-méthyle] / 5-Chlor-2-methyl-2,3-dihydro-isothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on [2-Methyl-2,3-dihydroisothiazol-3-on, 5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on]
MAK (OEL TWA) [1]	0.2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	0.4 mg/m ³ (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge
Notation	S, SS _C / S, SS _C
Regulatory reference	www.suva.ch, 28.03.2022

2-OCTYL-2H-ISOTHIAZOL-3-ONE (26530-20-1)

Austria - Occupational Exposure Limits

Local name	2-Octyl-2H-isothiazol-3-on
MAK (OEL TWA)	0.05 mg/m ³ (E)
OEL C	0.05 mg/m ³ (E)
Remark	H, S
Regulatory reference	BGBl. II Nr. 156/2021

Germany - Occupational Exposure Limits (TRGS 900)

AGW (OEL TWA) [1]	0.05 mg/m ³ (E)
Peak exposure limitation factor	2(I)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

Slovenia - Occupational Exposure Limits

Local name	2-oktil-2H-izotiazol-3-on
OEL TWA	0.05 mg/m ³
OEL STEL	0.1 mg/m ³
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021

North Macedonia - Occupational Exposure Limits

Local name	2-октил-2H-изотиазол-3-он
OEL TWA	0.05 mg/m ³ (I) инхалабилна фракција – дел на вкупно суспендирани материји, кои работникот ги вдишува
KTV	1
Short time value [mg/m ³]	0.05 mg/m ³

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

2-OCTYL-2H-ISOTHIAZOL-3-ONE (26530-20-1)	
Remark	(КТВ) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусно време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (К) својство на полесно пренесување на супстанците во организмот преку кожата; (Y)
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	2-n-Octyle-2,3-dihydroisothiazol-3-one / 2-n-Octyl-2,3-dihydroisothiazol-3-on
MAK (OEL TWA) [1]	0.05 mg/m ³ (i) / (e)
KZGW (OEL STEL)	0.1 mg/m ³ (i) / (e)
Critical toxicity	VRS / OAW
Notation	R, S / H, S
Regulatory reference	www.suva.ch, 28.03.2022
ZINC OXIDE (1314-13-2)	
Austria - Occupational Exposure Limits	
Local name	Zinkoxid-Rauch
MAK (OEL TWA)	5 mg/m ³ (A)
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Zinc (oxyde de) (fraction alvéolaire) # Zinkoxide (inadembare fractie)
OEL TWA	2 mg/m ³
OEL STEL	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Цинков оксид
OEL TWA	5 mg/m ³ (като цинк)
OEL STEL	10 mg/m ³ (като цинк)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
Local name	Cinkov oksid
GVI (OEL TWA) [1]	2 mg/m ³ R (respirabilna prašina)
KGVI (OEL STEL)	10 mg/m ³
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граничним vrijednostima izloženosti i biološkim граничним vrijednostima (NN 1/2021)

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

ZINC OXIDE (1314-13-2)	
Czech Republic - Occupational Exposure Limits	
Local name	Oxid zinečnatý, jako Zn
PEL (OEL TWA)	2 mg/m ³
NPK-P (OEL C)	5 mg/m ³
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Zinkoxid og zinkoxidrøg
OEL TWA [1]	4 mg/m ³ beregnet som Zn
Regulatory reference	BEK nr 2203 af 29. november 2021
Estonia - Occupational Exposure Limits	
Local name	Tsinkoksiid
OEL TWA	5 mg/m ³
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
Finland - Occupational Exposure Limits	
Local name	Sinkkioksidi, huurut
HTP (OEL TWA) [1]	2 mg/m ³
HTP (OEL STEL)	10 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Zinc (oxyde de)
VME (OEL TWA)	5 mg/m ³ (fumées) 10 mg/m ³ (poussières)
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Greece - Occupational Exposure Limits	
Local name	Ψευδαργύρου Οξείδιο (καπνοί)
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	CINK-OXID
AK (OEL TWA)	5 mg/m ³ por 5 mg/m ³ füst
Remark	i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármat); Por: N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok), füst: R (Azok az anyagok, amelyek egészségkárosító hatása RÖVID expozíció hatására jelentkezik)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

ZINC OXIDE (1314-13-2)	
Ireland - Occupational Exposure Limits	
Local name	Zinc oxide, fume
OEL TWA [1]	2 mg/m³ R (Respirable Fraction)
OEL STEL	10 mg/m³
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
Local name	Cinka oksīds
OEL TWA	0.5 mg/m³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumi Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumi Nr. 92)
Lithuania - Occupational Exposure Limits	
Local name	Cinko oksidas
IPRV (OEL TWA)	5 mg/m³
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Poland - Occupational Exposure Limits	
Local name	Tlenek cynku
NDS (OEL TWA)	5 mg/m³ w przeliczeniu na Zn: frakcja wdychalna
NDSch (OEL STEL)	10 mg/m³ w przeliczeniu na Zn: frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikać przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia.
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Óxido de zinco
OEL TWA	2 mg/m³ R (Fração respirável)
OEL STEL	10 mg/m³ R (Fração respirável)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Oxid de zinc
OEL TWA	5 mg/m³ (Fumuri)
OEL STEL	10 mg/m³ (Fumuri)
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Slovakia - Occupational Exposure Limits	
Local name	Oxid zinočnatý, dymy
NPHV (OEL TWA) [1]	1 mg/m³ respirabilná frakcia
NPHV (OEL STEL)	1 mg/m³ respirabilná frakcia
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Spain - Occupational Exposure Limits	
Local name	Óxido de cinc
VLA-ED (OEL TWA) [1]	2 mg/m³ Fracción respirable
VLA-EC (OEL STEL)	10 mg/m³ Fracción respirable

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

ZINC OXIDE (1314-13-2)	
Remark	d (Véase UNE EN 481: Atmósferas en los puestos de trabajo. Definición de las fracciones por el tamaño de las partículas para la medición de aerosoles).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
Local name	Zinkoxid
NGV (OEL TWA)	5 mg/m ³ totaldamm
Remark	3 (Med totaldamm menas de partiklar (aerosoler) som fastnar på ett filter i den provtagare som beskrivs i Metodserien, Provtagning av totaldamm och respirabelt damm, Metod nr 1010, Arbetskyddsstyrelsen, numera Arbetsmiljöverket. Filterdiameteren är normalt 37 mm, men kan även vara 25 mm. Trots sitt namn provtas inte den totala mängden luftburna partiklar med denna metod)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
Iceland - Occupational Exposure Limits	
Local name	Sínkoxíð og sínkoxíðreykur, sem Zn
OEL TWA	4 mg/m ³
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Sinkoksid
Grenseverdi (OEL TWA) [1]	5 mg/m ³
Regulatory reference	FOR-2021-06-28-2248
North Macedonia - Occupational Exposure Limits	
Local name	цинков оксид – дим
OEL TWA	5 mg/m ³ (A) алвеоларна фракција – дел на вдишани суспендирани материји, кои доспеваат до алвеолите
KTV	4
Short time value [mg/m ³]	20 mg/m ³
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусно време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	Oxyde de zinc (fumée) / Zinkoxid (Rauch)
MAK (OEL TWA) [1]	3 mg/m ³ (a) / (a)
KZGW (OEL STEL)	3 mg/m ³ (a) / (a)
Critical toxicity	Fimétal / Metallrauch
Remark	NIOSH, OSHA
Regulatory reference	www.suva.ch, 28.03.2022

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

ZINC OXIDE (1314-13-2)

USA - ACGIH - Occupational Exposure Limits

Local name	Zinc oxide
ACGIH OEL TWA	2 mg/m ³ (R - Respirable particulate matter)
ACGIH OEL STEL	10 mg/m ³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Metal fume fever
Regulatory reference	ACGIH 2022

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Various.
Odour	: Barely perceptible odour.
Odour threshold	: No data available
pH	: ≈ 8.5
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: $\approx 0\text{ }^{\circ}\text{C}$
Boiling point	: $\approx 100\text{ }^{\circ}\text{C}$
Flash point	: $> 100\text{ }^{\circ}\text{C}$
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: $\approx 1.33\text{ kg/l}$
Solubility	: Miscible with water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: $\approx 150.38\text{ mm}^2/\text{s}$
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: $\approx 25\text{ g/l}$
-------------	---------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
-----------------------	------------------

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

POLYPROPYLENE GLYCOL (25322-69-4)

LD50 oral rat	500 – 2000 mg/kg
LD50 dermal rat	> 3000 mg/kg
LD50 dermal rabbit	> 3000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 0.17 mg/l/4h Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)

LD50 dermal rat	> 1008 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
-----------------	---

PYRITHIONE ZINC (13463-41-7)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity)
-----------------	--

1,2-BENZISOTHIAZOLIN-3-ONE (2634-33-5)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
-----------------	--

2-OCTYL-2H-ISOTHIAZOL-3-ONE (26530-20-1)

LD50 oral rat	550 mg/kg
LD50 dermal	690 mg/kg

ZINC OXIDE (1314-13-2)

LD50 oral rat	> 15000 mg/kg
LD50 oral	7950 mg/kg

TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

Skin corrosion/irritation : Not classified
pH: ≈ 8.5

Additional information : 'Non-skin sensitising on the basis of the results on similar tested mixtures using bridging principles in accordance with CLP Regulation Article 9 (4);
OECD 429 LLNA (mouse) - non-skin sensitising - S4565

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)

pH	3.43 Temp.: 20 °C Concentration: 10 g/L
----	---

2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)

pH	2.58 Temp.: 25 °C Concentration: 50 g/L
----	---

Serious eye damage/irritation : Not classified
pH: ≈ 8.5

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)

pH	3.43 Temp.: 20 °C Concentration: 10 g/L
----	---

2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)

pH	2.58 Temp.: 25 °C Concentration: 50 g/L
----	---

Respiratory or skin sensitisation : Not classified

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

PYRITHIONE ZINC (13463-41-7)

LOAEL (animal/male, F1)	2.8 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
LOAEL (animal/female, F1)	1.4 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
NOAEL (animal/male, F1)	1.4 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
NOAEL (animal/female, F1)	0.7 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)

1,2-BENZISOTHIAZOLIN-3-ONE (2634-33-5)

NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
---------------------------	---

STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

POLYPROPYLENE GLYCOL (25322-69-4)

NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
----------------------------	--

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)

LOAEL (dermal, rat/rabbit, 90 days)	0.525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

PYRITHIONE ZINC (13463-41-7)

LOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
NOAEL (oral, rat, 90 days)	0.5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (dermal, rat/rabbit, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)

LOAEL (oral, rat, 90 days)	71.2 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: other:
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)

LOAEL (oral, rat, 90 days)	53.8 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

ONE CAN MATT

Viscosity, kinematic	≈ 150.38 mm ² /s
----------------------	-----------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Not rapidly degradable	

POLYPROPYLENE GLYCOL (25322-69-4)

LC50 - Fish [1]	> 100 mg/l
EC50 - Crustacea [1]	105.8 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	> 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)

LC50 - Fish [1]	0.19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	0.28 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	0.16 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.098 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'

PYRITHIONE ZINC (13463-41-7)

LC50 - Fish [1]	2.6 µg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	0.4 mg/l Test organisms (species): Cyprinodon variegatus
EC50 - Crustacea [1]	8.2 µg/l Test organisms (species): Daphnia magna

2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)

LC50 - Fish [1]	4.77 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	1.6 mg/l Test organisms (species): Daphnia magna

1,2-BENZISOTHIAZOLIN-3-ONE (2634-33-5)

LC50 - Fish [1]	≈ 16.7 mg/l Test organisms (species): Cyprinodon variegatus
LC50 - Fish [2]	2.15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	2.94 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	2.9 mg/l Test organisms (species): Daphnia magna

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

2-OCTYL-2H-ISOTHIAZOL-3-ONE (26530-20-1)

LC50 - Fish [1]	0.2 mg/l
EC50 - Other aquatic organisms [1]	2.6 mg/l
EC50 96h - Algae [1]	0.15 mg/l Test organisms (species):

TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)

LC50 - Fish [1]	0.14 – 5.59 mg/l
EC50 - Other aquatic organisms [1]	0.89 – 0.96 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code : 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 3082	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Transport document description				
UN 3082, III	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
	Not applicable	Not applicable	Not applicable	Not applicable

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
III	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: Yes	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : ≈ 25 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma

Germany

Employment restrictions

: Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Water hazard class (WGK)

: WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510)

: LGK 12 - Non-combustible liquids.

Joint storage table

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for

: LGK 1, LGK 6.2, LGK 7.

Joint storage with restrictions permitted for

: LGK 4.1A, LGK 4.3, LGK 5.1C.

Joint storage permitted for

: LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13.

Hazardous Incident Ordinance (12. BImSchV)

: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category

: Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioaccumulative potential/ toxicity or persistence)

SZW-lijst van kankerverwekkende stoffen

: None of the components are listed

SZW-lijst van mutagene stoffen

: None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

: None of the components are listed

SZW-lijst van reprotoxische stoffen –

: None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling

: PYRITHIONE ZINC is listed

Denmark

Danish National Regulations

: Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

Storage class (LK)

: LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Acute Tox. 1 (Inhalation)	Acute toxicity (inhal.), Category 1
---------------------------	-------------------------------------

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
EUH071	Corrosive to the respiratory tract.
EUH208	Contains A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9). May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Repr. 1B	Reproductive toxicity, Category 1B
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

ONE CAN MATT

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.