



ONE CAN OC64 - EGGSHELL

A quick-drying, low-odour, cross linking, water-thinned primer/ finish coat, with excellent adhesion, stain blocking and anti-corrosive properties. Prevents mould & mildew growth.

Recommended Areas of Use

For use as a low-odour, quick-drying, scuff and moisture resistant, adhesion promoting, stain-locking, anti-corrosive coating for interior or exterior walls and trim, masonry (Brickwork/Concrete etc) ferrous metals, non-ferrous metals, common plastics (e.g. melamine and uPVC), ceramic tiles, glass, wood and existing painted surfaces. Offers a hard-wearing, flexible coating with weather and light resistance, ideal for use over existing cladding coatings (coil, plastisol and powder coatings) with minimal preparation.

Properties

Gloss	Eggshell (approx. 25%)	Surface dry	30 Minutes
Theoretical Coverage	12m ² /L/coat	Minimum over coating time	1 hour minimum*
Recommended number of coats	2 coats minimum as a finish 3 coats for stain locking	Maximum over coating time	Unlimited
Density	1.24 kg/L	Minimum application conditions	10°C or above for application (minimum of 3°C above dew point)
Volume solids	41%	Full Cure	7 days
Flash point (Abel closed cup)	Non-Flammable	Shelf life	2 years minimum in original unopened containers.
VOC	30 g/L	Colour range	White & Black standard colours, Bradite Colour Card, RAL, British Standard, NCS.
Thinner / Cleaning	Water		
Recommended wet film thickness	75-100 microns/coat	Recommended dry film thickness	35 microns/coat

Suitable Surfaces

Suitable for use over most properly cleaned and prepared interior and exterior commercial wood, plastic and metals. Compatibility with existing coatings should be confirmed by preparing and painting a test patch. Anticorrosive for application to ferrous and non-ferrous metals which have been fully prepared. Seals most stains in the primer coat including water, nicotine, hardwood resin bleed, asphalt, and many more. This product is not suitable for use on Tom Howley kitchens. For guidance, please contact Tom Howley at clientservices@tomhowley.co.uk

Application Information

*Drying times will be prolonged at lower temperatures and over application.

All surfaces must be dry and dust free before coating. Application should always conform with the codes of practice described in BS 6150 and BS 5493. Film may take upto 7 days to fully cure, depending on number of coats, film thickness and local conditions. During this period, if rain/moisture is introduced to the coating watermarks may be visible. This will be more apparent in darker shades.

Brush and Roller - Supplied ready for use. Thin with 5-15% water if required.

Conventional Air Spraying - Thin with 5-15% water as required. Tip size - 2.0mm. Tip pressure - 60psi (0.4MPa) approximately. (Guidelines Only).

Airless Spraying - Thin with 5-15% water as required. Tip size - 19 thou (0.48mm) approximately. Tip pressure - 2100 psi (15MPa) approximately. (Guidelines Only).

Cleaning

Equipment should be cleaned immediately after use with water.

Surface Preparation

Loose and non-adhered coatings should be removed. Cleaning using Bradite Industrial Degreaser TD39 or methylated spirit is recommended to remove oils, grease and other contamination.

Intact areas of existing coatings should, ideally, be roughened by manual or mechanical sanding. If sanding, wear a suitable dust mask. Feather back any exposed areas to a sound coating edge. Cracks and pits should be filled using a suitable filler. Ensure the wall or ceiling is clean and completely dry, with a moisture content of <15 % before painting.

Mould: Caused by excess moisture and inadequate ventilation. Ensure the area is well-ventilated when applying paint and address any underlying humidity or airflow issues. If the root cause persists or is extensive, consider consulting a professional who specialises in mould and mildew remediation.

For anti-mould paint to be effective, proper preparation is essential. Treat the existing mould and do not paint over existing mould. Open windows for ventilation and wear protective gear, including gloves and mask, to avoid inhaling mould spores. Use a commercial fungicidal wash or a solution of one part bleach to three parts water to thoroughly clean the affected area. Thoroughly rinse the surface with clean water to remove residue and allow it to dry completely.

Stain locking: Encapsulates stains in the primer coat, application of second coat will be required to hide, and in extreme cases a third coat may be required. One Can should be allowed to hard dry prior to overcoating. This will take at least one hour, over application may result in longer drying times

Aluminum, stainless steel, galvanised steel, copper and other metals: Cleaned and degreased with methylated spirit, and lightly abraded if possible. White salts on weathered galvanising must be removed during cleaning and degreasing. Light surface rusting should be treated with Bradite Rust Convertor RC46. Heavy rusting to be removed to clean metallic finish (SIS-St 3).

New Wood: Ensure moisture content of the timber is below 15% before commencing application. Damp wood should never be painted as this may give rise to blistering, flaking, cracking and premature coating failure. Knots to be wiped using methylated spirit, for heavy or active knots spot prime with aluminium wood primer.

Hard Woods: Wipe with methylated spirit to remove excess resin, changing the face of the cloth regularly. Lightly abrade.

Green oak: Should not be painted unless it has been weathered for at least 6 months.

Exterior cladding, Powder coated, Varnish and Existing paint finish: Remove all loose and flaking paintwork. Degrease using Bradite Industrial Degreaser TD39, followed by clean water rinse. Rub down thoroughly with a medium grade sandpaper to provide a key and a defect free smooth surface, "feathering in" areas where paint has been removed.

UPVC, Formica, Melamine and Plastics: For long term performance, degrease using Bradite Industrial Degreaser TD39 or methylated spirit & lightly abrade surfaces.

New plaster walls: For plaster skim, allow at least four weeks for the plaster to thoroughly dry. Apply a primer coat by thinning the paint with a 5 to 25% (v/v) addition of clean water, depending upon the porosity of the substrate. Cut in by brushing at the same dilution recommendation as for priming, to promote flow and sealing of the substrate.

For new, fully plastered walls, allow at least six months for the plaster to thoroughly dry before painting.

This product is not recommended for painting lime or other natural plasters.

Masonry, brick, concrete: Clean, dry and free of contamination, existing coatings to be sound and well adhered. Any loose flaking material should be removed and sanded back to a sound, well-feathered edge. New concrete or masonry to be fully cured. Mould or mildew to be removed and area treated with good quality fungicidal wash following manufacturer's instructions.

Painting System

1st coat	Bradite ONE CAN OC64
2nd coat	Bradite ONE CAN OC64
3rd coat	Bradite ONE CAN OC64 [If required]

Certificates & Approvals

Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems. 2004/42/EC EU limit value for this product (Annex IIA/i. wb): 140g/l (2010). This product contains max 30 g/l VOC.

Fire Classification:

One Can has a fire classification of Class E/Efl (for walls/ceilings) or (for flooring) under EN 13501-1. This indicates that it resists low flame ignition for a short period and does not produce a large flame spread. It offers a basic level of fire retardancy compared to higher classes (B, C, D)*.

Typical application areas:

Wall and Ceiling Linings: Plasterboard, plaster, brick, and concrete.

Timber Products: Hardwood, softwood, and engineered boards.

Previously Painted Surfaces: Suitable for covering old, non-retardant paint layers.

Fire Classification Summary:

One Can has been tested and classified in accordance with EN 13501-1:2018, achieving a fire classification of E / Efl.

- Tested according to the EN ISO 11925-2: 2020 ignitability test
- Test specimen is brought into contact with a propane gas flame with a height of 2 mm and at an angle of 45°
- Flame spread ≤ 150 mm within 20 seconds, following a 15-second flame

Summary Safety Information

Always refer to the Health and Safety sheet for the product before use, and observe the warning phrases on the label. In general, avoid inhalation of spray mist and skin contact by the use of masks, gloves and other personal protection. Eyes should be copiously washed with water or proprietary wash, and medical attention obtained. Skin should be thoroughly washed using a cleanser and soap and water.

Disclaimer - The information on this data sheet is correct to the best of our knowledge and experience. Bradite reserves the right to modify data contained herein, without notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service and application may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.

*Report available upon request.

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Mixture
Product name	: ONE CAN EGGSHELL
Product code	: OC64
Type of product	: Paint
Product group	: End product

1.2. Relevant identified uses of the substance or mixture and uses advised against**Relevant identified uses**

Main use category	: Consumer use
Function or use category	: Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Bradite Paints
Ogwen Valley Works
Bethesda
Gwynedd
LL57 4YP
T +44 (0)1248 600315, F +44 (0)1248 602782
sales@bradite.com

1.4. Emergency telephone number

Emergency number : +44 (0)1248 600315

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazardous to the aquatic environment – Chronic Hazard, H411
Category 2
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS09

Hazard statements (CLP)	: H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P273 - Avoid release to the environment. P391 - Collect spillage. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EUH208 - Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5). May produce an allergic reaction.

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Comments : Advanced Micro Matrix Embedding (AMME™) technology: Algicide/Fungicide based on following substances: Terbutryn, pyrithione zinc, 2-Octyl-2H-isothiazol-3-one, zinc oxide, 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
TRIZINC BIS(ORTHOPHOSPHATE)	CAS-No.: 7779-90-0 EC-No.: 231-944-3 EC Index-No.: 030-011-00-6 REACH-no: 01-2119485044-40	< 5	STOT RE 2, H373 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
ZINC OXIDE substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DK, EE, ES, FI, GR, HR, HU, IE, LT, LV, PL, PT, RO, SE, SK, IS, NO, MK, CH)	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030-013-00-7 REACH-no: 01-2119463881-32	< 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	< 5	Acute Tox. 4 (Oral), H302 (ATE=450 mg/kg bodyweight) Acute Tox. 2 (Inhalation:dust,mist), H330 (ATE=0.21 mg/l) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
PYRITHIONE ZINC	CAS-No.: 13463-41-7 EC-No.: 236-671-3 EC Index-No.: 613-333-00-7	0.011 (0.0037)	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)
TERBUTRYN	CAS-No.: 886-50-0 EC-No.: 212-950-5	0.016 (0.0016)	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-OCTYL-2H-ISOTHIAZOL-3-ONE	CAS-No.: 26530-20-1 EC-No.: 247-761-7 EC Index-No.: 613-112-00-5	0.009 (0.0009)	Acute Tox. 4 (Oral), H302 (ATE=550 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=311 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 Acute Tox. 2 (Inhalation:dust,mist), H330 (ATE=0.27 mg/l) Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071
A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6]	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	< 5	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) EUH071
2-METHYLISOTHIAZOL-3(2H)-ONE	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50	< 5	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 1 (Inhalation), H330 (ATE=0.005 mg/l/4h) Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1) EUH071

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6	(0.036 ≤ C ≤ 100) Skin Sens. 1A; H317
2-OCTYL-2H-ISOTHIAZOL-3-ONE	CAS-No.: 26530-20-1 EC-No.: 247-761-7 EC Index-No.: 613-112-00-5	(0.0015 ≤ C ≤ 100) Skin Sens. 1A; H317
A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6]	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	(0.0015 ≤ C < 100) Skin Sens. 1; H317 (0.06 ≤ C ≤ 0.6) Skin Irrit. 2; H315 (0.06 ≤ C ≤ 0.6) Eye Irrit. 2; H319 (0.6 ≤ C < 100) Skin Corr. 1B; H314

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
2-METHYLISOTHIAZOL-3(2H)-ONE	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9 REACH-no: 01-2120764690-50	(0.0015 ≤ C ≤ 100) Skin Sens. 1A; H317

Comments : Contains 2-methylisothiazol-3(2H)-one and 1,2-benzisothiazol-3(2H)-one to maintain storage stability. The percentages "total (free)%" of terbutryn are indicated. The free proportion is subject to the classification of the mixture with regard to environmentally hazardous properties, sensitisation. The percentages "total (free)%" of 2-octyl-2H-isothiazol-3-one are indicated. The free proportion is subject to the classification of the mixture with regard to environmentally hazardous properties, skin and eye irritation, sensitisation. The percentages "total (free)%" of pyrithione zinc are indicated. The free proportion is subject to the classification of the mixture with regard to environmentally hazardous properties, skin and eye irritation. Hazard statements see section 16

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.
Self protection of the first-aider : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : None under normal conditions.
Symptoms/effects after eye contact : None under normal conditions.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Keep cool. Protect from sunlight.
Packaging materials : Always store product in container of same material as original container.

Germany

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

Joint storage table

LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

Joint storage not permitted for : LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.2, LGK 4.3, LGK 5.1B, LGK 5.1C, LGK 5.2

Joint storage permitted for : LGK 2B, LGK 3, LGK 4.1B, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

7.3. Specific end use(s)

Coatings and paints, thinners, paint removers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)

Switzerland - Occupational Exposure Limits

Local name	2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle et 2,3-dihydro-isothiazol-3-one de 2-méthyle [2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle, 2,3-Dihydro-isothiazol-3-one de 2-méthyle] / 5-Chlor-2-methyl-2,3-dihydro-isothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on [2-Methyl-2,3-dihydroisothiazol-3-on, 5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on]
MAK (OEL TWA)	0.2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	0.4 mg/m ³ (i) / (e)
Notation	S, SS _C / S, SS _C
Regulatory reference	www.suva.ch, 18.06.2025

2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)

Austria - Occupational Exposure Limits

Local name	2-Methyl-2,3-di-hydroisothiazol-3-on
MAK (OEL TWA)	0.05 mg/m ³
Remark	Sh
Regulatory reference	BGBl. II Nr. 330/2024

2-OCTYL-2H-ISOTHIAZOL-3-ONE (26530-20-1)

Austria - Occupational Exposure Limits

Local name	2-Octyl-2H-isothiazol-3-on
MAK (OEL TWA)	0.05 mg/m ³ (E)
OEL C	0.05 mg/m ³ (E)
Remark	H, S
Regulatory reference	BGBl. II Nr. 330/2024

Germany - Occupational Exposure Limits (TRGS 900)

Local name	2-Octyl-2H-isothiazol-3-on
AGW (OEL TWA)	0.05 mg/m ³ (E)
Peak exposure limitation factor	2(I)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

Slovenia - Occupational Exposure Limits

Local name	2-oktil-2H-izotiazol-3-on
------------	---------------------------

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2-OCTYL-2H-ISOTHIAZOL-3-ONE (26530-20-1)	
OEL TWA	0.05 mg/m ³
OEL STEL	0.1 mg/m ³
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
Regulatory reference	Uradni list RS, št. 26/2025 z dne 18.4.2025 - Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
North Macedonia - Occupational Exposure Limits	
Local name	2-октил-2H-изотиазол-3-он
OEL TWA	0.05 mg/m ³ (l) инхалабилна фракција – дел на вкупно суспендирани материји, кои работникот ги вдишува
KTV	1
OEL STEL*	0.05 mg/m ³
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (K) својство на полесно пренесување на супстанците во организмот преку кожата; (Y)
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)
Switzerland - Occupational Exposure Limits	
Local name	2-n-Octyle-2,3-dihydroisothiazol-3-one / 2-n-Octyl-2,3-dihydroisothiazol-3-on
MAK (OEL TWA)	0.05 mg/m ³ (i) / (e)
KZGW (OEL STEL)	0.1 mg/m ³ (i) / (e)
Notation	R, S / H, S
Regulatory reference	www.suva.ch, 18.06.2025
*STEL value is calculated based on the TWA limit	
ZINC OXIDE (1314-13-2)	
Austria - Occupational Exposure Limits	
Local name	Zinkoxid-Rauch
MAK (OEL TWA)	5 mg/m ³ (A)
Regulatory reference	BGBl. II Nr. 330/2024
Belgium - Occupational Exposure Limits	
Local name	Zinc (oxyde de) (fraction alvéolaire) # Zinkoxide (inadembare fractie)
OEL TWA	2 mg/m ³
OEL STEL	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Bulgaria - Occupational Exposure Limits	
Local name	Цинков оксид
OEL TWA	5 mg/m ³ (като цинк)

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ZINC OXIDE (1314-13-2)	
OEL STEL	10 mg/m ³ (като цинк)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 28 от 2024 г., в сила от 05.04.2024 г.)
Croatia - Occupational Exposure Limits	
Local name	Cinkov oksid
GVI (OEL TWA)	2 mg/m ³ R (respirabilna prašina)
KGVI (OEL STEL)	10 mg/m ³
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, граниčnim vrijednostima izloženosti i biološkim граниčnim vrijednostima (NN 148/2023)
Czech Republic - Occupational Exposure Limits	
Local name	Oxid zinečnatý, jako Zn
PEL (OEL TWA)	2 mg/m ³
NPK-P (OEL C)	5 mg/m ³
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 20/2025 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Zinkoxid og zinkoxidrøg
8-timers grænseværdi (OEL TWA)	4 mg/m ³ beregnet som Zn
Korttidsgrænseværdi (OEL STEL)*	8 mg/m ³ beregnet som Zn
Regulatory reference	BEK nr 1619 af 19/12/2024
Estonia - Occupational Exposure Limits	
Local name	Tsinkoksiid
OEL TWA	5 mg/m ³
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 02.04.2024, 13)
Finland - Occupational Exposure Limits	
Local name	Sinkkioksiidi, huurut
HTP (OEL TWA)	2 mg/m ³
HTP (OEL STEL)	10 mg/m ³
Regulatory reference	HTP-ARVOT 2025 (Sosiaali- ja terveysministeriö)
Greece - Occupational Exposure Limits	
Local name	Ψευδαργύρου Οξειδίο (καπνοί)
OEL TWA	5 mg/m ³
OEL STEL	10 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	CINK-OXID
AK (OEL TWA)	5 mg/m ³ por 5 mg/m ³ füst

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ZINC OXIDE (1314-13-2)	
Remark	i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármat); Por: N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok), füst: R (Azok az anyagok, amelyek egészségkárosító hatása RÖVID expozíció hatására jelentkeznek)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Zinc oxide, fume
OEL TWA	2 mg/m ³ R (Respirable Fraction)
OEL STEL	10 mg/m ³
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024
Latvia - Occupational Exposure Limits	
Local name	Cinka oksīds
OEL TWA	0.5 mg/m ³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2024. gada 26. martā noteikumiem Nr. 191).
Lithuania - Occupational Exposure Limits	
Local name	Cinko oksidas
IPRV (OEL TWA)	5 mg/m ³
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Poland - Occupational Exposure Limits	
Local name	Tlenek cynku
NDS (OEL TWA)	5 mg/m ³ w przeliczeniu na Zn – frakcja wdychalna
NDSch (OEL STEL)	10 mg/m ³ w przeliczeniu na Zn – frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która stwarza zagrożenie dla zdrowia po zdeponowaniu w drogach oddechowych.
Regulatory reference	Dz. U. 2024 poz. 1017 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Óxido de zinco
OEL TWA	2 mg/m ³ R (Fração respirável)
OEL STEL	10 mg/m ³ R (Fração respirável)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Oxid de zinc
OEL TWA	5 mg/m ³ (Fumuri)
OEL STEL	10 mg/m ³ (Fumuri)
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 179/2024)
Slovakia - Occupational Exposure Limits	
Local name	Oxid zinočnatý, dymy
NPHV (OEL TWA)	1 mg/m ³ respirabilná frakcia

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ZINC OXIDE (1314-13-2)	
NPHV (OEL STEL)	1 mg/m ³ respirabilná frakcia
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (122/2024 Z. z.)
Spain - Occupational Exposure Limits	
Local name	Óxido de cinc
VLA-ED (OEL TWA)	2 mg/m ³ Fracción respirable
VLA-EC (OEL STEL)	10 mg/m ³ Fracción respirable
Remark	d (Véase UNE EN 481: Atmósferas en los puestos de trabajo. Definición de las fracciones por el tamaño de las partículas para la medición de aerosoles).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2025. INSHT
Sweden - Occupational Exposure Limits	
Local name	Zinkoxid
NGV (OEL TWA)	5 mg/m ³ (totaldamm)
Remark	25 (Med inhalerbar och respirabel fraktion menas de dammfractioner som definieras i svensk standard SS-EN 481, Arbetsplatsluft – Partikelstorleksfraktioner för mätning av luftburna partiklar (utgåva 1, 1993). Med totaldamm menas de partiklar (aerosoler) som fastnar på ett filter i en totaldammprovtagare)
Regulatory reference	Arbetsmiljöverkets föreskrifter och allmänna råd (AFS 2023:14) om gränsvärden för luftvägsexponering i arbetsmiljön
Iceland - Occupational Exposure Limits	
Local name	Sínkoxíð og sínkoxíðreykur, sem Zn
OEL TWA	4 mg/m ³
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Norway - Occupational Exposure Limits	
Local name	Sinkoksid
Grenseverdi (OEL TWA)	5 mg/m ³
Regulatory reference	FOR-2024-04-05-581
North Macedonia - Occupational Exposure Limits	
Local name	цинков оксид – дим
OEL TWA	5 mg/m ³ (A) алвеоларна фракција – дел на вдишани суспендирани материји, кои доспеваат до алвеолите
KTV	4
OEL STEL*	20 mg/m ³
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ZINC OXIDE (1314-13-2)	
Switzerland - Occupational Exposure Limits	
Local name	Oxyde de zinc (fumée) / Zinkoxid (Rauch)
MAK (OEL TWA)	3 mg/m ³ (a) / (a)
KZGW (OEL STEL)	3 mg/m ³ (a) / (a)
Remark	NIOSH, OSHA
Regulatory reference	www.suva.ch, 18.06.2025
USA - ACGIH® - Threshold Limit Values	
Local name	Zinc oxide
ACGIH® TLV® TWA	2 mg/m ³ (R - Respirable particulate matter)
ACGIH® TLV® STEL	10 mg/m ³ (R - Respirable particulate matter)
Remark (ACGIH®)	TLV® Basis: Metal fume fever
Regulatory reference	ACGIH 2025

*STEL value is calculated based on the TWA limit

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Various.

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Appearance	: Liquid.
Odour	: Barely perceptible odour.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: ≈ 0 °C
Boiling point	: ≈ 100 °C
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 100 °C
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available
pH	: ≈ 8.5
Viscosity, kinematic	: ≈ 145.16 mm ² /s
Solubility	: Miscible with water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: ≈ 1.24 kg/l
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content : ≈ 32 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)	
LD50 dermal rat	> 1008 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
PYRITHIONE ZINC (13463-41-7)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity)
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
2-OCTYL-2H-ISOTHIAZOL-3-ONE (26530-20-1)	
LD50 oral rat	550 mg/kg
LD50 dermal	690 mg/kg
ZINC OXIDE (1314-13-2)	
LD50 oral rat	> 15000 mg/kg
LD50 oral	7950 mg/kg
TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)	
LD50 oral rat	> 5000 mg/kg
Skin corrosion/irritation	: Not classified pH: ≈ 8.5
Additional information	: 'Non-skin sensitising on the basis of the results on similar tested mixtures using bridging principles in accordance with CLP Regulation Article 9 (4); OECD 429 LLNA (mouse) - non-skin sensitising - S4565
A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)	
pH	3.43 Temp.: 20 °C Concentration: 10 g/L
2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)	
pH	2.58 Temp.: 25 °C Concentration: 50 g/L
Serious eye damage/irritation	: Not classified pH: ≈ 8.5
A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)	
pH	3.43 Temp.: 20 °C Concentration: 10 g/L
2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)	
pH	2.58 Temp.: 25 °C Concentration: 50 g/L
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
PYRITHIONE ZINC (13463-41-7)	
LOAEL (animal/male, F1)	2.8 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
LOAEL (animal/female, F1)	1.4 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

PYRITHIONE ZINC (13463-41-7)	
NOAEL (animal/male, F1)	1.4 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
NOAEL (animal/female, F1)	0.7 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
NOAEL (animal/female, F0/P)	112 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)	
LOAEL (dermal, rat/rabbit, 90 days)	0.525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

PYRITHIONE ZINC (13463-41-7)	
LOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
NOAEL (oral, rat, 90 days)	0.5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (dermal, rat/rabbit, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)	
LOAEL (oral, rat, 90 days)	71.2 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: other:
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)	
LOAEL (oral, rat, 90 days)	53.8 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

ONE CAN EGGSHELL	
Viscosity, kinematic	≈ 145.16 mm ² /s

11.2. Information on other hazards

No additional information available

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)

LC50 - Fish [1]	0.19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	0.28 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	0.16 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.098 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'

PYRITHIONE ZINC (13463-41-7)

LC50 - Fish [1]	2.6 µg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	0.4 mg/l Test organisms (species): Cyprinodon variegatus
EC50 - Crustacea [1]	8.2 µg/l Test organisms (species): Daphnia magna

2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)

LC50 - Fish [1]	4.77 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	1.6 mg/l Test organisms (species): Daphnia magna

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

LC50 - Fish [1]	≈ 16.7 mg/l Test organisms (species): Cyprinodon variegatus
LC50 - Fish [2]	2.15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	2.94 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	2.9 mg/l Test organisms (species): Daphnia magna

2-OCTYL-2H-ISOTHIAZOL-3-ONE (26530-20-1)

LC50 - Fish [1]	0.2 mg/l
EC50 - Other aquatic organisms [1]	2.6 mg/l
EC50 96h - Algae [1]	0.15 mg/l Test organisms (species):

TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)

LC50 - Fish [1]	0.14 – 5.59 mg/l
EC50 - Other aquatic organisms [1]	0.89 – 0.96 mg/l

12.2. Persistence and degradability

ONE CAN EGGSHELL

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 247-500-7] AND 2-METHYL-2H-ISOTHIAZOL-3-ONE [EC NO 220-239-6] (55965-84-9)	
Persistence and degradability	Not rapidly degradable
PYRITHIONE ZINC (13463-41-7)	
Persistence and degradability	Not rapidly degradable
TERBUTRYN (886-50-0)	
Persistence and degradability	Not rapidly degradable
2-METHYLISOTHIAZOL-3(2H)-ONE (2682-20-4)	
Persistence and degradability	Not rapidly degradable
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
Persistence and degradability	Not rapidly degradable
2-OCTYL-2H-ISOTHIAZOL-3-ONE (26530-20-1)	
Persistence and degradability	Not rapidly degradable
ZINC OXIDE (1314-13-2)	
Persistence and degradability	Not rapidly degradable
TRIZINC BIS(ORTHOPHOSPHATE) (7779-90-0)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
European List of Waste (LoW, EC 2000/532)	: 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11






SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Orange plates : 

Tunnel restriction code (ADR) : -
EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 375, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A97, A158, A197, A215
ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601, 650
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : ≈ 32 g/l

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Denmark

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with it.
If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.

Finland

France

Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
- VOC content : ≈ 32 g/l

Netherlands

- ABM category : Z(1) - non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioacumulative potential/ toxicity or persistence)
- SZW-lijst van kankerverwekkende stoffen : None of the components are listed
- SZW-lijst van mutagene stoffen : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : PYRITHIONE ZINC is listed

Poland

- Polish National Regulations : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as amended)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:	
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstracts Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:

TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Full text of H- and EUH-statements:

Acute Tox. 1 (Inhalation)	Acute toxicity (inhal.), Category 1
Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H360D	May damage the unborn child.

ONE CAN EGGSHELL

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5). May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.